

ROMAC DUCTILE IRON SERVICE SADDLES

PAINTED SADDLE WITH U-BOLT

Recommended for asbestos-cement, cast iron or steel pipe.



ALSO AVAILABLE IN DOUBLE STRAP

MATERIAL SPECIFICATIONS

SADDLE CASTINGS: Ductile (nodular) iron, ASTM A-536-80, grade 65-45-12, protected with corrosion resistant paint.

GASKETS: Virgin SBR compounded for water and sewer service.

STRAPS, WASHERS and NUTS: Mayari-R (Corten) high tensile strength, low alloy steel.

PAINTED SADDLE WITH STAINLESS STEEL STRAP

Stainless Steel Strap recommended for P.V.C. pipe.



ALSO AVAILABLE IN DOUBLE STRAP

MATERIAL SPECIFICATIONS

SADDLE CASTINGS: Ductile (nodular) iron. ASTM A-536-80, grade 65-45-12, protected with corrosion resistant paint.


STAINLESS STEEL STRAP: Bolts, nuts, and washers: 5/8" N.C. roll thread Teflon coated. Band: 2" wide for "spreading out" clamp force on pipe. M.I.G. welds are passivated for resistance to corrosion. All the above type 304 (18-8) stainless steel.

GASKETS: Virgin SBR compounded for water and sewer service.

This submittal has been reviewed for compliance with general requirements of design and arrangement only, and is not a contract

NYLON SADDLE WITH STAINLESS STEEL STRAP

Recommended for asbestos-cement, cast iron, steel, or P.V.C. pipe in hot or corrosive soils, the contractor.



ALSO AVAILABLE IN DOUBLE STRAP

MATERIAL SPECIFICATIONS SALES TO BE

SADDLE CASTINGS: Ductile (nodular) iron, ASTM A-536-80, grade 65-45-12, covered by black nylon fused coat, approximately 10 - 12 mils thick, with approximate dielectric strength of 1,000 v/mil.

STAINLESS STEEL STRAP: Bolts, nuts, and washers: 5/8" N.C. roll thread Teflon coated. Band: 2" wide for "spreading out" clamp force on pipe M.I.G. welds are passivated for resistance to corrosion. All the above type 304 (18-8) stainless steel.

GASKETS: Virgin SBR compounded for water and sewer service.



Date To S